

Material Safety Data Sheet

TRADE NAME: PELEMOL GMB

Date of Preparation: 11/20/2009

Section 1 - Chemical Product and Company Identification

Product Name: PELEMOL GMB
Chemical Name: Glyceryl Behenate
CAS Number: 30233-64-8
Manufacturer: PHOENIX CHEMICAL, INC.
 60 Fourth Street, Somerville, New Jersey 08876
 Phone (908) 707-0232, Fax (908) 707-0186

CHEMTREC 24-HR EMERGENCY RESPONSE
 NUMBER: 1-800-424-9300
 INTERNATIONAL CALLS: COLLECT
 1-703-527-3887
 CHEMTREC should only be called in the event of
 chemical emergencies involving a spill, leak, fire,
 exposure, or accident involving chemicals.

Section 2 - Composition / Information on Ingredients

This product does not contain any active material considered hazardous as defined in 29 CFR 1910.120

Ingredient Name	CAS Number	% wt/vol
Glyceryl Behenate	30233-64-8	100 %

Trace Impurities:

Ingredient	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
None Known	None Estab.	None Estab.	Not Estab.	Not Estab.	Not Estab.	Not Estab.	Not Estab

Section 3 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Potential Health Effects

There are no potential health effects expected from handling this material. Good manufacturing practices are always recommended when handling any chemical.
 A knowledge of the available toxicology information and of the physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.
 This material is registered with TSCA.
 Exposure to small quantities is not expected to cause adverse health effects.
 There are no significant laboratory data to suggest any specific hazard to humans.

HMIS

H	1
F	0
R	0
PPE	B

Inhalation: Short-term harmful health effects are not expected from vapor-generated at ambient temperatures.
Eye Contact: May cause some moderate eye irritation.
Skin Contact: May cause some irritation or discomfort.
Ingestion: May cause abdominal discomfort, nausea, vomiting and diarrhea.
Carcinogenicity: IARC, NTP, and OSHA do not list this product as a carcinogen.

Section 4 - First Aid Measures

Inhalation: Short-term harmful health effects are not expected from vapor-generated at ambient temperatures. If first aid is required, move victim to fresh air.

Eye Contact: May cause some moderate eye irritation. Flush immediately with water for 15 to 20 minutes. Obtain medical attention if severe irritation occurs.

Skin Contact: May cause some irritation or discomfort. Remove contaminated clothing. Wash affected area with soap & water.

Ingestion: May cause abdominal discomfort, nausea, vomiting and diarrhea. Give two glasses of water. Do not induce vomiting. Obtain medical attention.

After first aid, get appropriate in-plant, paramedic, or community medical support.

PELEMOL GMB

Section 5 - Fire-Fighting Measures


Flash Point: >150°C

Flash Point Method: PMCC

Extinguishing Media: Use water spray, carbon dioxide, alcohol type or universal type foam applied in accordance with the manufacturer's instructions.

Fire-Fighting Instructions: Treat as an oil fire. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.



Section 6 - Accidental Release Measures

Safeguards (Personnel): Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean up.

Spill/Leak Procedures: Collect for disposal in accordance with applicable Federal, State, or local regulations.

Containment: For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: (Personnel) Safety glasses and PVC gloves.

Storage Requirements: Keep container tightly closed.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: No special engineering controls are required under normal use.

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec.2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear an MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear a SCBA.

Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Solid

Appearance and Odor: Flake or Granules, practically odorless

Vapor Pressure, mm Hg: <0.1 mm Hg @ 20°C

Vapor Density (Air=1): N/A

Density: N/A

Specific Gravity (H₂O=1, @ 25°C): approx. 0.9

pH: 4-6

Water Solubility: Dispersible (hot)

Boiling Point: >200°C

Freezing/Melting Point: approx. 70°C

Viscosity: Solid

Refractive Index: N/D

% Volatile: Nil

Evaporation Rate: N/A

Section 10 - Stability and Reactivity

Stability: Product is **STABLE** at room temperature in closed containers under normal storage and handling conditions.

Chemical Incompatibilities: Avoid strong acids, alkalis and oxidizers.

Hazardous Thermal Decomposition Products: Oxides of Carbon.

Hazardous Polymerization: Will not occur.

Normal Shelf Life: One year minimum, if kept sealed.

PELEMOL GMB

Section 11- Toxicological Information

A knowledge of the available toxicology information and of the chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

Section 12 - Ecological Information

N/A

Section 13 - Disposal Considerations

Disposal: Contact a licensed contractor for detailed recommendations. Follow applicable Federal, State, and local regulations.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101):

DOT Proper Shipping Name: Not Regulated

DOT I.D. #: N/A

DOT Classification: N/A

UN Hazard Class: N/A

Section 15 - Regulatory Information

TSCA Inventory Status: Listed

EPA Regulations: SARA 311/312 Codes:

- Acute: None
- Chronic: None
- Fire: None
- Reactivity: None
- Pressure: None

State Regulations:

State	Component	CAS #	Wt.
NONE			

Section 16 - Other Information

Prepared by: PHOENIX CHEMICAL, INC., 60 Fourth Street, Somerville, NJ 08876, Phone: 908-707-0232

Disclaimer: While the information herein is believed to be reliable, PHOENIX CHEMICAL, INC. does not guarantee its accuracy. Purchasers are urged to conduct their own tests. PHOENIX CHEMICAL, INC. warrants its materials, as described herein, shall conform to the written specifications for such materials. PHOENIX CHEMICAL, INC. makes no other warranty, either express or implied, as to the materials' merchantability or fitness for purpose. In no event shall PHOENIX CHEMICAL, INC.'s liability for breach of this warranty exceed the purchase price of the material for which such breach is claimed. Nothing contained herein is intended as a recommendation to use PHOENIX CHEMICAL, INC. products so as to infringe any patent and no liability for customer's violation of patent or other rights is assumed.